SAFETY DATA SHEET

HYBRID 🛠 A G

Opti-Trace Copper

Hybrid-Ag Pty Ltd

Catalogue number: N/A Version No: 0.1 Issue date: 19/03/2021 Safety Data Sheet according to WHS and ADG requirements

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product name	Opti-Trace Copper
Synonyms	NA
Other means of identification	Liquid Fertiliser, Copper Liquid
elevant identified uses of t	he substance or mixture and uses advised against
Relevant identified uses	Fertiliser, soil stimulation
etails of the manufacturer/	
etails of the manufacturer/ Registered company name	
	/importer
Registered company name	/importer Hybrid-Ag Pty Ltd
Registered company name Address	/importer Hybrid-Ag Pty Ltd 52 Buckler Road, Wangaratta, VIC 3677
Registered company name Address Telephone	/importer Hybrid-Ag Pty Ltd 52 Buckler Road, Wangaratta, VIC 3677

Association / Organisation	Poisons Information Centre
Emergency telephone numbers	13 1126
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

Poisons Schedule	S6			
GHS Classification ^[1]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Acute Aquatic Hazard Category 1, Chronic			
	Aquatic Hazard Category 1			
abel elements				
GHS label elements				
SIGNAL WORD	WARNING			
lazard statement(s)				
H302	Harmful if swallowed.			
H315	Causes skin irritation.			
H319	Causes serious eye irritation.			
H410	Very toxic to aquatic life with long lasting effects.			
Precautionary statement(s) P	revention			
P270	Do not eat, drink or smoke when using this product.			
P273	Avoid release to the environment.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			

Precautionary statement(s) Response

P321	Specific treatment (see advice on this label)			
P362	ke off contaminated clothing and wash before reuse.			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing			
P337+P313	e irritation persists: Get medical advice/attention.			
P391	ollect spillage			
P301+P312	F SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.			
P302+P352	F ON SKIN: Wash with plenty of water.			
P330	Rinse mouth.			
P332+P313	If skin irritation occurs: Get medical advice/attention.			

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

Dispose of contents and containers in accordance with local regulations

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

All ingredients are non-hazardous

Mivturo

Mixtures		
CAS No	% (weight)	Name
N/A	100	Proprietary Liquid Nutrient Fertiliser Mix

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

For copper intoxication:

Unless extensive vomiting has occurred empty the stomach by lavage with water, milk, sodium bicarbonate solution or a 0.1% solution of potassium ferrocyanide (the resulting copper ferrocyanide is insoluble).

Administer egg white and other demulcents.

Maintain electrolyte and fluid balances.

Morphine or meperidine (Demerol) may be necessary for control of pain.

If symptoms persist or intensify (especially circulatory collapse or cerebral disturbances, try BAL intramuscularly or penicillamine in accordance with the supplier's recommendations.

Treat shock vigorously with blood transfusions and perhaps vasopressor amines.

If intravascular haemolysis becomes evident protect the kidneys by maintaining a diuresis with mannitol and perhaps by alkalinising the urine with sodium bicarbonate. It is unlikely that methylene blue would be effective against the occassional methaemoglobinemia and it might exacerbate the subsequent haemolytic episode. Institute measures for impending renal and hepatic failure

[GOSSELIN, SMITH & HODGE: Commercial Toxicology of Commercial Products]

None known

A role for activated for charcoals or emesis is, as yet, unproven.

In severe poisoning CaNa2EDTA has been proposed. [ELLENHORN & BARCELOUX: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

Water spray or fog, Foam, Dry chemical powder, BCF (where regulations permit), Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire incompatibility

Advice for firefighters

Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use
Fire/Explosion Hazard	Non combustible. Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of: sulfur oxides (SOx) and metal oxides

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Environmental hazard - contain spillage. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment and dust respirator. Prevent spillage from entering drains, sewers or water courses. Recover product wherever possible. Avoid generating dust. Sweep / shovel up. If required, wet with water to prevent dusting. Put residues in labelled plastic bags or other containers for disposal. Wash area down with large quantity of water and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.
	Personal protective equipment advice is contained in Section 8 of this SDS

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	Glass container is suitable for laboratory quantities. Polyethylene or polypropylene container. Check all containers are clearly labelled and free from leaks.				
Storage incompatibilities	Copper sulfate: reacts violently with strong bases, hydroxylamine.(with ignition), magnesium (producing hydrogen gas). In contact with potassium chlorate is poter explosive. Solutions are acidic and can react with metals to evolve flammable hydrogen gas corrosive to some metals including steel. Incompatible with sulfuric caustics, ammonia, aliphatic amines, alkanolamines, amides, alkylene oxides, epichlorohydrin, organic anhydrides, isocyanates, vinyl acetate. Dusts or mists may n with acetylene to form shock-sensitive copper acetylides				
	$\land \land \land \land$				



 Must not be stored together
May be stored together with specific preventions
May be stored together X 0 +

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

1			
OCCUPATIONAL	EXPOSUBE	LIMITS	

- INGREDIENT DATA
- Not Available

EMERGENCY LIMITS

Ingredient	Material Name		TEEL-1	TEEL-2	TEEL-3
copper sulfate pentahydrate	Copper sulfate; (Copper(II) sulfate)		7.5 mg/m3	10 mg/m3	59 mg/m3
copper sulfate pentahydrate	Copper(II) sulfate pentahydrate		12 mg/m3	32 mg/m3	190 mg/m3
Ingredient	Original IDLH	Revised IDLH			
copper sulfate pentahydrate	Not Available	Not Available			

OCCUPATIONAL EXPOSURE BANDING		
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
copper sulfate pentahydrate	E	≤ 0.01 mg/m ³
	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the	
Notes:	adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a	
NOTES.	range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant. Type of Contaminant: Air Speed: Solvent, vapours, degreasing etc., evaporating from tank (in still air) - Air Speed: 0.25-0.5 m/s (50-100 f/min) Aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, picklii (released at low velocity into zone of active generation) - Air Speed: 0.25-1 m/s (100-200 f/min). Direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) - Air Speed: 1-2.5 m/s (200-500 f/min) Grinding, abrasive blasting, tumbing, high speed wheel generated dusts (released at high initial velocity in
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.
Personal protection	
Eye and face protection	Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This sho include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly.
Skin protection	See Hand protection below
Hands/feet protection	Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	Overalls. P.V.C. apron. Barrier cream. Skin cleansing cream. Eye wash unit.

Respiratory protection

Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
P1	-	PAPR-P1
Air-line*		
Air-line**	P2	PAPR-P2
-	P3	-
	Air-line*	-
-	Air-line**	PAPR-P3
	P1 Air-line* Air-line**	P1 Air-line* Air-line** P2 - P3 Air-line*

Allal classes = Organice Gentaria = Continuous now Allal classes = Organice (HCN), B = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Dark brown to black liquid		
Physical state	Liquid	Specific Gravity (Water = 1)	1.179
Odour	Low to no odour	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable

pH (as supplied)	4-8	Decomposition temperature	Not Applicable
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit(%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Fully Miscible	pH as a solution	48
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particula are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be
conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. Copper poisoning following exposure to copper dusts and fume may result in headache, cold sweat and weak pulse. Capillary, kidney, liver and brain damage are the longer term manifestations of such poisoning. Inhalation of freshly formed metal oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever". Symptoms may be delayed for up to 12 hours and begin with the sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalise feeling of malaise. Mild to severe headache, nausea, occasional vomiting, fever or chills, exaggerated mental activity, profuse sweating, diarrhoea, excessive urination and prostration may also occur. Tolerance to the fumes develops rapidly, but is quickly lost. All symptoms usually subside within 24-36 hours following removal from exposure.
Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damay to the health of the individual. Sulfates are not well absorbed orally, but can cause diarrhoea. A metallic taste, nausea, vomiting and burning feeling in the upper stomach region occur after ingestion of copper and its derivatives. The vomitus is usually green/blue and discolours contaminated skin.
This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition. Oper cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Exposure to copper, by skin, has come from its use in pigments, ointments, ornaments, jewellery, dental amalgams and IUDs (intra-uterine devices), and in killing fungi and algae. Although copper is used in the treatment of water in swimming pools and reservoirs, there are no reports of toxicity from these applications.
This material can cause eye irritation and damage in some persons. Copper salts, in contact with the eye, may produce inflammation of the conjunctiv or even ulceration and cloudiness of the cornea.
Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Substance accumulation in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung. For copper and its compounds (typically copper choride): Acute toxicity: There are no reliable acute or all toxicity results available. Animal testing shows that skin in exposure to copper may lead to hardness of the skin, scar formation, exudation and reddish changes. Inflammation, irritation and injury of the skin were noted. Repeat dose toxicity: Animal testing shows that very high levels of copper monochloride may cause anaemia. Genetic toxicity: Copper monochloride does not appear to cause mutations in vitro, although chromosomal aberrations were seen at very high concentrations in vitro. Cancer-causing potential: There was insufficient information to evaluate the cancer-causing activity of copper monochloride.

COPPER SULFATE, PENTAHYDRATE	for copper and its compounds (typically copper chloride): Acute toxicity: There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw. Symptom of the hardness of skin, an exudation of hardness site, the formation of scar and reddish changes were observed on application sites in all treated animals. Skin inflammation and injury were also noted. In addition, a reddish or black urine was observed in females at 2,000, 1,500 and 1,000 mg/kg bw. Female rats appeared to be more sensitive than male based on mortality and clinical signs. No reliable skin/eye irritation studies were available. The acute dermal study with copper monochloride suggests that it has a potential to cause skin irritation. Repeat dose toxicity: In repeated dose toxicity study performed according to OECD TG 422, copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39 - 51 days to females at concentrations of 0, 13, 50, 20, and 80 mg/kg bw/day. The NOAEL value was 5 and 13 mg/kg bw/day for male and female rats, ne treatment-related death was observed in female rats in the high dose group. Erythropoietic toxicity (anaemia) was seen in both sexes at the 80 mg/kg bw/day. The frequency of squamous cell hyperplasia of the forestomach was increased in a dose-dependent manner in male and female rats at all treatment groups, and was statistically significant in males at doses of =20 mg/kg bw/day and in females at doses of =5 mg/kg bw/day doses. The observed effects are considered to be local, non-systemic effect on the forestomach which result from oral (gavage) administration of copper monochloride. Genotoxicity: An in vi

COPPER SULFATE. PENTAHYDRATE

The NOAEL of copper monochloride for fertility toxicity was 80 mg/kg bw/day for the parental animals. No treatment-related effects were observed on the reproductive organs and the fertility parameters assessed. For developmental toxicity the NOAEL was 20 mg/kg bw/day. Three of 120 pups appeared to have icterus at birth; 4 of 120 pups appeared runted at the highest dose tested (80 mg/kg bw/day). For copper sulfate Copper sulfate is conosive. Side effects are diverse and multi-systemic, and include severe gastrointestinal symptoms and signs, metallic taste in the mouth, burning pain in the chest, headache, sweating, shock and damage to brain, liver and kidneys. It has been reported as a cause of human suicide. On exposure, it can cause dose dependent damage to the skin and eye, also, eczema and allergic reactions. Long term effects can lead to anaemia and degenerative changes and are more likely in individuals with Wilson's disease, a condition which causes excessive absorption and storage of copper. It has adverse effects on reproduction and fertility as well as cancer and embryo toxic effects. Although it is excreted in the faeces, there is residual accumulation the liver, brain, heart, kidney and muscles.

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

copper sulfate, pentahydrate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.001-mg/L	2
	EC50	72	Algae or other aquatic plants	0.0165mg/L	2
	NOEC	768	Fish	0.0048mg/L	2
Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
copper sulfate, pentahydrate	HIGH	HIGH

Bio accumulative potential

Ingredient Bio	lioaccumulation
copper sulfate, pentahydrate LOV	OW (LogKOW = -2.2002)

Mobility in soil

Ingredient	Mobility
copper sulfate, pentahydrate	LOW (KOC = 6.124)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / packaging disposal	Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill.
------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required		
Marine Pollutant		
HAZCHEM	22	

....

and transport (ADG):	
UN number	3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains copper sulfate, pentahydrate)
Transport hazard class(es)	Class: 9
	Subrisk: Not Applicable
Packing group	
Environmental hazard	Environmentally hazardous
Special precautions for user	Special provisions: 274 331 335 375 AU01
	Limited quantity: 5 kg
Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082	

are not subject to this Code when transported by road or rail in;

(a) packagings;

(b) IBCs; or

(c) any other receptacle not exceeding 500 kg(L). - Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

Air transport (ICAO-IATA / DGR)	
UN number	3077
UN proper shipping name	Environmentally hazardous substance, solid, n.o.s. * (contains copper sulfate, pentahydrate)
Transport hazard class(es)	ICAO/IATA Class: 9
	ICAO / IATA Subrisk: Not Applicable
	ERG Code: 9L
Packing group	II
Environmental hazard	Environmentally hazardous
Special precautions for user	Special provisions: A97 A158 A179 A197
	Cargo Only Packing Instructions: 956
	Cargo Only Maximum Qty / Pack: 400 kg
	Passenger and Cargo Packing Instructions: 956
	Passenger and Cargo Maximum Qty / Pack: 400 kg
	Passenger and Cargo Limited Quantity Packing Instructions: Y956
	Passenger and Cargo Limited Maximum Qty / Pack: 30 kg G

Sea transport (IMDG-Code / GGVSee)

Sea transport (imbo-code /	001566
UN number	3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains copper sulfate, pentahydrate)
Transport hazard class(es)	IMDG Class: 9
	IMDG Subrisk: Not Applicable
Packing group	H
Environmental hazard	Marine Pollutant
Special precautions for user	EMS Number: F-A , S-F
	Special provisions: 274 335 966 967 969
	Limited quantities: 5 kg

Transport in bulk according to Annex II of MARPOL and the IBC code. Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture COPPER SULFATE, PENTAHYDRATE IS FOUND ON THE FOLLOWING REGULATORY LISTS Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS) Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -

Appendix A

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 4

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule $\mathbf{6}$

International Air Transport Association (IATA) Dangerous Goods Regulations International Maritime Dangerous Goods Requirements (IMDG Code)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (copper sulfate, pentahydrate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks

may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA;	Permissible Concentration-Time Weighted Average
PC-STEL:	Permissible Concentration-Short Term Exposure Limit
IARC:	International Agency for Research on Cancer
ACGIH:	American Conference of Government Industrial Hygienists
STEL:	Short Term Exposure Limit
TEEL:	Temporary Emergency Exposure Limit
IDLH:	Immediate Danger to Life or Health Concentrations
OSF:	Odour Safety Factor
NOAEL:	No Observed Effects Level
TLV:	Threshold Limit Value
LOD:	Limit Of Detection
OTV:	Odour Threshold Value
BCE:	Bio Concentration Eactors
BCF:	Bio Concentration Factors
BEI:	Biological Exposure Index

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission

End of SDS